


# MetraSCAN3D™

FAST AND ACCURATE  
3D SCANNER AND PORTABLE CMM  
FOR THE SHOP FLOOR



# MetraSCAN3D™

## SPEED AND ACCURACY COMBINED WITH VERSATILITY

Fast, accurate, and versatile, the MetraSCAN 3D™ optical CMM scanner line-up is designed for manufacturing and metrology professionals who want to deliver approved quality parts quickly and efficiently.

Insensitive to shop floor vibrations, part movement, and environmental instability, the MetraSCAN 3D significantly increases the efficiency, reliability, and versatility of measurement processes. Engineered to work both in the metrology lab and on the production floor, the MetraSCAN 3D is optimized to perform metrology-grade measurements and 3D surface inspections on a large variety of parts regardless of size, material, finish, or complexity. Simply put, the MetraSCAN 3D is the ideal metrology tool for quality control and quality assurance applications.

When paired with the HandyPROBE™, which offers optional probing capability, users can harness the power of both 3D scanning and probing for a complete, streamlined inspection process.



**ACCURACY OF  
0.025 mm**



**PATENTED  
TECHNOLOGY**




**CERTIFIED  
ISO 17025**



**WORLDWIDE  
SUPPORT**



- 1 High-performance optics**  
Optimal scan quality
- 2 Extra single laser line**  
Easy capture of hard-to-reach areas
- 3 Blue laser technology**  
High-resolution capability
- 4 Stand-off distance color indicator**  
Maximizes scanning performance
- 5 Multifunction buttons**  
Quick access to frequently used software functionalities
- 6 Visibility indicators**  
Scanner, probe, and reference visibility
- 7 Continuous environment monitoring**  
Tracking of calibration artifacts
- 8 HandyPROBE**  
Optional probing capability



### SPEED

The MetraSCAN 3D features 15 laser crosses and a high measurement rate to provide accelerated scanning time. From quick setup to real-time meshing and ready-to-use files, the measurement workflow has never been faster. The time savings in data measurement, acquisition, and analysis is simply impressive!

**High measurement rate**

Up to 1,800,000 measurements/second

**Large scanning area**

15 laser crosses

**Quick setup**

Up and running in less than 2 minutes

No warm-up time



### ACCURACY & RESOLUTION

Free from any rigid measurement setup requirements, the MetraSCAN 3D is designed specifically for use on the shop floor. Accredited ISO 17025 and compliant with the VDI/VDE 2634 part 3 standard, the MetraSCAN 3D delivers accurate results, regardless of the measurement setup quality and the user's experience level. Thanks to the C-Track™ optical tracker that enables dynamic referencing, the scanner, the part and the optical tracker can move during inspection and still provide accurate measurements.

**Accuracy**

0.025 mm

**Volumetric accuracy**

0.064 mm

**Reliable acceptance test**

Based on VDI/VDE 2634 part 3 standard  
ISO 17025 accredited laboratory

**Shop floor accuracy with dynamic referencing**

Measurement accuracy insensitive to environmental instabilities

**High resolution**

Masters complex and highly detailed parts



### VERSATILITY

Highly versatile, the MetraSCAN 3D can be used to scan various part sizes and surface finishes in real time—all with the same device. With its extendable measurement volume, parts of any shape, complexity, and geometry can be measured easily without loss in accuracy or conventional leapfrog. When combined with the HandyPROBE, the measurement system acquires even more versatility: probing for geometrical entities and 3D scanning for complete surface inspection.

**Blue laser technology**

Ideal for shiny and reflective surfaces

**Large and easily extendable measurement volume**

Wider than other portable CMMs

No leapfrog required

**Optional HandyPROBE**

Combination of both 3D scanning and probing

No target required

# TECHNICAL SPECIFICATIONS

Innovating technology that provides accuracy, simplicity, portability as well as real speed to your metrology-grade applications.

	MetraSCAN 357™	MetraSCAN BLACK™	MetraSCAN BLACK™ Elite
<b>ACCURACY</b> <sup>(1)</sup>	Up to 0.040 mm	0.035 mm	0.025 mm
<b>VOLUMETRIC ACCURACY</b> <sup>(2)</sup>	9.1 m <sup>3</sup>	0.086 mm	0.064 mm
	16.6 m <sup>3</sup>	0.122 mm	0.078 mm
<b>VOLUMETRIC ACCURACY WITH MaxSHOT Next™ Elite</b> <sup>(3)</sup>	0.060 mm + 0.015 mm/m		0.044 mm + 0.015 mm/m
<b>PROBING ACCURACY WITH HandyPROBE Next</b> <sup>(4)</sup>	Up to 0.030 mm	0.030 mm	0.025 mm
<b>MEASUREMENT RESOLUTION</b>	0.100 mm	0.025 mm	
<b>MESH RESOLUTION</b>	0.200 mm	0.100 mm	
<b>MEASUREMENT RATE</b>	480,000 measurements/s	800,000 measurements/s	1,800,000 measurements/s
<b>LIGHT SOURCE</b>	7 red laser crosses	7 blue laser crosses	15 blue laser crosses (+ 1 extra line)
<b>LASER CLASS</b>	2M (eye safe)		
<b>SCANNING AREA</b>	275 x 250 mm	310 x 350 mm	
<b>STAND-OFF DISTANCE</b>	300 mm		
<b>DEPTH OF FIELD</b>	200 mm	250 mm	
<b>PART SIZE RANGE</b> (recommended)	0.2–6 m		
<b>SOFTWARE</b>	VXelements		
<b>OUTPUT FORMATS</b>	.dae, .fbx, .ma, .obj, .stl, .txt, .wrl, .x3d, .zpr, .3mf		
<b>COMPATIBLE SOFTWARE</b> <sup>(5)</sup>	3D Systems (Geomagic® Solutions), InnovMetric Software (PolyWorks), Metrologic Group (Metrolog X4), New River Kinematics (Spatial Analyzer), Verisurf, Dassault Systèmes (CATIA V5, SOLIDWORKS), PTC (Creo), Siemens (NX, Solid Edge), Autodesk (Inventor, PowerINSPECT)		
<b>WEIGHT</b>	Scanner: 1.38 kg Probe: 0.5 kg C-Track: 5.7 kg	Scanner: 1.49 kg Probe: 0.5 kg C-Track: 5.7 kg	
<b>DIMENSIONS</b> (LxWxH)	Scanner: 289 x 235 x 296 mm Probe: 68 x 157 x 340 mm C-Track: 1031 x 181 x 148 mm		
<b>OPERATING TEMPERATURE RANGE</b>	5–40 °C		
<b>OPERATING HUMIDITY RANGE</b> (non-condensing)	10–90%		
<b>CERTIFICATIONS</b>	EC Compliance (Electromagnetic Compatibility Directive, Low Voltage Directive), compatible with rechargeable batteries (when applicable), IP50, WEEE		
<b>PATENTS</b>	FR 2,838,198, EP (FR, UK, DE, IT) 1,492,995, US 7,487,063, CA 2,529,044		

(1) MetraSCAN BLACK and MetraSCAN BLACK|Elite (ISO 17025 accredited): Based on VDI/VDE 2634 part 3 standard. Probing error performance is assessed with diameter measurement on traceable sphere artefacts.

MetraSCAN 357: Typical value for diameter measurement on a calibrated sphere artefact.

(2) MetraSCAN BLACK and MetraSCAN BLACK|Elite (ISO 17025 accredited): Based on VDI/VDE 2634 part 3 standard. Sphere-spacing error is assessed with traceable length artefacts by measuring these at different locations and orientations within the working volume.

MetraSCAN 357: Value for sphere spacing measurement on calibrated length artefacts.

(3) The volumetric accuracy performance of the system when using a MaxSHOT 3D cannot be superior to the default volumetric accuracy performance for a given model.

(4) HandyPROBE Next and HandyPROBE Next|Elite performance assessment (ISO 17025 accredited) is based on partial procedure per ISO 10360-12 standard: *Probing size error* (6.2) and *Length error* (6.4). Performance is assessed on traceable sphere and length artefacts.

(5) Also compatible with all major metrology, CAD, and computer graphic software through mesh and point cloud import.



**AMETEK GmbH**  
**Division Creaform Deutschland**  
 Meisenweg 37  
 D - 70771 Leinfelden-Echterdingen  
 T.: +49 711 1856 8030 | F.: +49 711 1856 8099

[creaform.info.germany@ametek.com](mailto:creaform.info.germany@ametek.com) | [creaform3d.com](http://creaform3d.com)



Authorized Distributor

MetraSCAN 3D, MetraSCAN BLACK, MetraSCAN BLACK|Elite, MetraSCAN 357, HandyPROBE, HandyPROBE Next, C-Track, MaxSHOT Next|Elite, VXelements, and their respective logo are trademarks of Creaform Inc. © Creaform Inc. 2020. All rights reserved. V1